

MODEL GO1700A SPEED INCREASER

Product Description

Model GO1700A is a single-stage increasing gearbox designed for direct mounting to industrial engines via an SAE flange and driven in standard engine rotation (CW facing input shaft). Tabulated below are nominal power and speed capacity together with standard options. Contact Cotta to discuss other options or specialized requirements.

OUTPUT ROTATION:	Opposite to input.
MAX INPUT TORQUE:	5500 lb-ft.
MAX INPUT SPEED:	2500 RPM or as otherwise limited by input clutch or coupling.
MAX OUTPUT SPEED:	5500
RATIO RANGE:	1.5 to 3.0
OUTPUT SHAFT SIZE:	2.750" diameter X 6.0" long with 5/8" X 5/16" keyway.
OUTPUT SHAFT LOCATION:	12 o'clock to input std. 3, 6, and 9 o'clock optional.
SAE FLANGE OPTIONS:	#00, #0, #1
*FLYWHEEL COUPLINGS:	Various clutches, couplings, and drive plates through SAE 24".
REAR SUPPORT:	Required. Customer supplied item. Mounting holes provided per drawing.
LUBRICATION:	Integral Lube pump supplied.
COOLING:	Oil/water shell-and-tube cooler furnished if required. Various options.
**SIDE LOAD CAPABLE:	No. Contact Cotta for recommendations.
***APPROXIMATE WEIGHT:	1900 lbs.

^{*} Flywheel coupling selection requires Cotta technical review and approval.

www.cotta.com • 608-368-5600 • sales@cotta.com

^{**} Cotta Speed Increaser output shafts are not designed for belt or chain side pull drives. If your application requires side loads provide complete application details to Cotta for recommendations and approval.

^{***} Weight listed is an average. Actual weight can vary significantly with options such as SAE housing size and flywheel coupling choices.

